

Sanlixin Solenoid Valve

SLM 2/2-way Pilot Operate Piston Solenoid Valve

Main Technical Parameters

Serialized products, small in size, Large flow rate, widely use

Body material: Brass

Plunger tube material: brass stainless steel

Voltage: AC220V/6VA DC24V/6W (other voltage can special made)

Flow as the arrow, mounts in any position

Best position is solenoid vertical and upright direction

This series valve are offered NBR EPDM VITON for series and diaphragm to provide on-off control of various fluids.



Pipe Size	Orifice mm	CV	Working Pressure (bar)				Coil Type	Power		Coil Class	Model code LxWxH	Model Code Follows Voltage are AC220V 50/60HZ	Weight Kg	
			Min	Max		VA AC 220V		W DC 24V						
				Gas					Liquid					
				AC	DC				AC					DC
3/8"	12	2.4	0.5	16	12	16	12	D	6	6	F	62x43x84.2	0.44	
	12	2.4	0.5	16	12	16	12	D	6	6	F	62x43x84.2		
	12	2.4	0.5	16	12	16	12	D	6	6	F	62x43x84.2		
1/2"	12	2.4	0.5	16	12	16	12	D	6	6	F	62x43x84.2	0.42	
	12	2.4	0.5	16	12	16	12	D	6	6	F	62x43x84.2		
	12	2.4	0.5	16	12	16	12	D	6	6	F	62x43x84.2		
3/4"	20	6.0	0.5	16	12	16	12	D	6	6	F	80x60x93	0.8	
	20	6.0	0.5	16	12	16	12	D	6	6	F	80x60x93		
	20	6.0	0.5	16	12	16	12	D	6	6	F	80x60x93		
1"	25	8.5	0.5	16	12	16	12	D	6	6	F	100x80x102	1.0	
	25	8.5	0.5	16	12	16	12	D	6	6	F	100x80x102		
	25	8.5	0.5	16	12	16	12	D	6	6	F	100x80x102		

Configuration dimension chart

