

Sanlixin Solenoid Valve

SLY 2/2-Way Solenoid Valve · Normally open

2-Way normally open solenoid valve, Open when de-energized, Closed when energized.
Serialized products, small in size, large flow rate, widely use

- 1: Voltage: AC220V/50Hz DC24V
- 2: Working pressure: 0~30bar
- 3: Orifice: $\Phi 1.0-\Phi 2.5\text{mm}$
- 4: Fluids Temp: 0-120°C
- 5: Body material: brass SS
- 6: This series valves are offered NBR、VITON、EPDM



Construction, External Dimensions Chart

1	2	3	4	5	6	7	8	9	10
Valve Series	Mode of Operation	Coil Type	Coil Class	Voltage	Seal Material	Body Material	connect size	Orifice (mm)	Options
SLY	2	D	F	02	N	1	A	C2	
	2= Normally open	D: DIN Standard Connections, Fully Encapsulated S= NASS Coil	F=F Class H=H Class	02= AC220V 01= AC110V 13= DC24V	N= NBR E= EPDM V= VITON	1= brass 3= SS304	A= G1/8" B= G1/4"	01=1.0 C1=1.2 C2=1.5 02=2.0 C3=2.5	A= Thread in body B= Thread out body N=NPT

SLY 2/2-Way Solenoid Valve • Normally open

Valve Selection List

Connect	Orifice mm	Operating pressure differential (Bar)			Coil Type	Coil power		Coil Class	Model Code Follows Voltage AC220V/50Hz	Weight kg
		Min.	Max.			VA	W			
			Air	Water		AC220V	DC24V			
G1/8	Φ1.0	0	30	30	D	22	13	F	SLY2DF02N1A01	0.25
G1/8	Φ1.2	0	30	30	D	22	13	F	SLY2DF02N1AC1	0.25
G1/8	Φ1.5	0	30	30	D	22	13	F	SLY2DF02N1AC2	0.25
G1/8	Φ2.0	0	15	12	D	22	13	F	SLY2DF02N1A02	0.25
G1/8	Φ2.5	0	13	10	D	22	13	F	SLY2DF02N1AC3	0.25

External Dimensions Chart

