

## SLX Timer Switch Device

### Analog electronil timer

Working voltage: 24-220V AC/DC 50HZ/60HZ  
 Static electricity: 4mA Max  
 Working temperature: -10°C~+50°C  
 Protection level: IP65-EN 60529  
 Keeping voltage: 400V Max  
 Capanty: 1A  
 Instantaneous current: 10A for 10ms  
 Electrify efficiency: 100%ED  
 The life time of switch: 3 × 10<sup>8</sup>  
 Time ON: form 0.5 ~10s  
 Time OFF: form 0.5 ~ 45min  
 Indicator: yellowLED  
 Connection type: DIN43650A



### Digital electronic timer

- 1 : High quality flame retardant plastic shell,high strength and security
- 2: Microcomputer chip control,powerful, high precision
- 3: LED digital tube display with night vision fuction.
- 4: Time adjustment :range:two-way adjustable time switch,  
 ON time 1Sec ~ 9min59Sec;  
 OFF time 1Sec ~ 99h59min59Sec
- 5 : Function mode: loop mode (two ways: first on then off or first off then on);  
 Single mode (one way: specified time on).
- 6 : Power supply:high-voltage AC/DC 110~240V (XY-3800H)  
 Low-voltage AC/DC 7~36V(XY-3800L)
- 7 : Protection IP65 When properly installed
- 8 : The standard DIN43650A input and output interfaces.
- 9 : If indicator is light, it is ON state, otherwise it is the OFF state.
- 10 : Field of use: solenoid valve controlling and other similar timing application

