

Sanlixin Solenoid Valve

SLP Small Series 2/2-way Direct Acting Solenoid Valve · Normally Closed

- 1: 2/2 way normally closed , closed when de-energized , open when energized
- 2: Max pressure tolerance: 15 kgf/cm²
- 3: Ambient temp : 0~65℃
- 4: Flow as the arrow ,mounts in any position ; best position is solenoid vertical and upright direction
- 5: Only 3/8" connection size ,orifice 3 and 4mm , can be widely used in the corresponding flow and pressure system , replace the same connection size but big orifice valve , can save a lot of cost
- 6: Voltage : AC220V/230V/240V/110V/24V 50/60HZ DC24V/12V
- 7: Seals : Can choose NBR、EPDM、VITON to fit to control of different media;
- 8: Coil can fix SM Coil. AC 220V/AC110V/AC24V/DC24V



Valve Selection List

Pipe Conn-ection	Orifice mm	CV Factor	Operating pressure Differential (kgf/cm ²)				Max. Temp. °C	Coil Type	Power consumption		Coil Class	Model Code Follows Voltage are 220VAC50/60HZ		
			Min.	Max.		AC 220V			DC 24V					
				Air、 Gas water、 Hotwater liquid						Light oil				
				AC	DC					AC			DC	
3/8"	3	0.3	0	13	13	10	10	80	D	22	13	F	SLP1DF02N1C03	SLP1DF02N3C03
	3	0.3	0	13	13	10	10	130	D	22	13	F	SLP1DF02E1C03	SLP1DF02E3C03
	3	0.3	0	13	13	10	10	120	D	22	13	F	SLP1DF02V1C03	SLP1DF02V3C03
	4	0.6	0	8	8	6	6	80	D	22	13	F	SLP1DF02N1C04	SLP1DF02N3C04
	4	0.6	0	8	8	6	6	130	D	22	13	F	SLP1DF02E1C04	SLP1DF02E3C04
	4	0.6	0	8	8	6	6	120	D	22	13	F	SLP1DF02V1C04	SLP1DF02V3C04

N.W:0.34kg

External Dimensions:

