

# Sanlixin Solenoid Valve

## SLP Plastic Series 2/2-way Pilot Operated Solenoid Valve • Normally Closed

- 1:** 2-Way normally closed solenoid valve, Closed when de-energized, open when energized.
- 2:** Body material: (PA6)
- 3:** Max. Allowable pressure 13kgf/cm<sup>2</sup>; Ambient Temp. 0°C~65°C
- 4:** Serialized products, small in size, large flow rate, widely use
- 5:** Flow as the arrow, mounts in any position; Best position is Solenoid vertical and upright direction.
- 6:** Voltage: 220VAC/230VAC/240VAC/110VAC/24VAC 50/60HZ 24VDC/12VDC;  
Voltage Tolerance: +10% to -10% applicable voltage
- 7:** This series valves are offered NBR、VITON、EPDM etc  
for Seals and diaphragm to provide on-off control of various fluids.
- 8:** Coil can fix SM Coil. AC 220V/AC110V/AC24V/DC24V



### Valve Selection List

Pipe Conn-ection	Orifice mm	CV Factor	Min.	Operating pressure differential (kgf/cm <sup>2</sup> ) Max.			Max. Fluids Temp.	Coil Type	Power consumption		Coil Class	External Dimensions Length x Width x Height A x B x H	Model Code Follows Voltage Are 220VAC 50/60HZ	Weight (KG)
				Air Gas	Water Hot water Liquids	Light oil ≤ 20CST			VA	W				
3/8"	13	4.5	0.5	10	10	6	80	D	22	13	F	76×52×112	SLP1DF02N7C13	0.38
	13	4.5	0.5	10	10		80	D	22	13	F	76×52×112	SLP1DF02E7C13	0.38
	13	4.5	0.5	10	10	6	80	D	22	13	F	76×52×112	SLP1DF02V7C13	0.38
1/2"	13	4.5	0.5	10	10	6	80	D	22	13	F	76×52×112	SLP1DF02N7D13	0.37
	13	4.5	0.5	10	10		80	D	22	13	F	76×52×112	SLP1DF02E7D13	0.37
	13	4.5	0.5	10	10	6	80	D	22	13	F	76×52×112	SLP1DF02V7D13	0.37
3/4"	20	7.6	0.5	10	10	6	80	D	22	13	F	90×71×116	SLP1DF02N7E20	0.43
	20	7.6	0.5	10	10		80	D	22	13	F	90×71×116	SLP1DF02E7E20	0.43
	20	7.6	0.5	10	10	6	80	D	22	13	F	90×71×116	SLP1DF02V7E20	0.43
1"	25	12	0.5	10	10	6	80	D	22	13	F	111×91×123	SLP1DF02N7G25	0.49
	25	12	0.5	10	10		80	D	22	13	F	111×91×123	SLP1DF02E7G25	0.49
	25	12	0.5	10	10	6	80	D	22	13	F	111×91×123	SLP1DF02V7G25	0.49
1 1/4"	35	22	0.5	10	10	6	80	D	22	13	F	158×115×141	SLP1DF02N7H35	0.85
	35	22	0.5	10	10		80	D	22	13	F	158×115×141	SLP1DF02E7H35	0.85
	35	22	0.5	10	10	6	80	D	22	13	F	158×115×141	SLP1DF02V7H35	0.85
1 1/2"	40	30	0.5	10	10	6	80	D	22	13	F	158×115×141	SLP1DF02N7J40	0.78
	40	30	0.5	10	10		80	D	22	13	F	158×115×141	SLP1DF02E7J40	0.78
	40	30	0.5	10	10	6	80	D	22	13	F	158×115×141	SLP1DF02V7J40	0.78